

Homestead Finishing Products
1935 W 96th St. Unit Q
Cleveland, OH 44102
216-631-5309

MATERIAL SAFETY DATA SHEET

ViviTone Solvent Pigment Dispersion - All Colors

EMERGENCY TELEPHONE NUMBER: 216-631-5309
PREPARATION DATE: 10/24/2001
REVISION DATE: 8/2/2010
PREPARED BY: JEFF JEWITT

I. PRODUCT IDENTIFICATION

Trade Name(s)	ViviTone Solvent Micro-pigment Dispersion (All colors)
Chemical Name	N/A
Color Index Name	Proprietary Pigment mixture
Chemical Family	
Chemical Formula	Proprietary
TSCA	In compliance

II. HAZARDOUS INGREDIENTS

COMPONENTS	CAS #	%	OSHA PEL	OSHA STEL
Isopropanol	000067-63-0	30%	400 ppm TWA	
Dipropylene Glycol Monomethyl Ether	34590-94-8	18%	100 ppm TWA	
Ethanol	64-17-5	32%	1000 ppm TWA	
Methanol	67-56-1	7%	200 ppm TWA	

III. PHYSICAL DATA

Appearance and Odor	Various bright colors, alcohol odor
Solubility in Water	Slight, with precipitation

IV. FIRE AND EXPLOSION DATA

Flash Point	60 F
Extinguishing Media	Water mist, dry chemical, CO2
Special Procedures for Fire Fighting	Wear Self Contained Breathing Apparatus
Unusual Hazards	Flammable! Vapor is heavier than air and may travel to a flash point. Use water fog to cool containers and prevent rupturing. Burning may produce oxides of carbon and nitrogen, chlorine compounds as well as other toxic gases and vapors

V. REACTIVITY DATA

Stability	Stable.
Conditions to Avoid	None known
Polymerization	Will not occur.

MSDS – VIVITONE SOLVENT PIGMENT DISPERSION

VI. HEALTH HAZARDS

This product is expected to be a low ingestion hazard.
This product may cause drying, cracking or irritation to skin.
May cause mild eye irritation
Inhalation of vapor may cause drowsiness and irritation.

As with all chemicals, avoid prolonged or unnecessary contact.

Contact with skin or eyes may cause irritation

This product is **not** listed by NTP or OSHA as a carcinogen.

VII. EMERGENCY FIRST AID PROCEDURES

Inhalation - If inhaled, move to fresh air. If difficulty in breathing, administer oxygen and get immediate medical attention.

Ingestion – No emergency care is anticipated. If swallowed give several glasses water.

Eye Contact - Flush with flowing water for at least 15 minutes. Get immediate medical attention

Skin Contact - Wash affected area with soap and water. If irritation persists, get medical attention.
Remove and launder clothing before reuse.

VIII. SPILL AND LEAK PROCEDURES

Contain and clean up spill immediately and place in disposal container.

Dispose of waste according to federal, state or local regulations.

IX. SPECIAL PROTECTION INFORMATION

Respiratory OSHA approved respirator for organic vapors

Ventilation Local exhaust to minimize exposure

Protective Gloves Wear Rubber or Neoprene gloves

Eye Protection Wear chemical safety goggles

Other Wear appropriate equipment to prevent exposure and personal contact. Eyewash fountain should be easily accessible. After handling material, wash hands thoroughly. Wash work clothes before reuse.

X. SPECIAL PRECAUTIONS

In accordance with good industrial practice, handle with care and avoid personal contact.

XI. SHIPPING DATA

DOT Status Regulated as Class III Packing Group II Paint related Material

XII. HMIS RATING

Health 1
Fire 3
Reactivity 0
Protection X

DISCLAIMER: J.B. Jewitt Co., Inc., Homestead Finishing Products believes all the information and data given is accurate as of the date of preparation and is offered in good faith, but without warranty or representation. Since conditions of use are beyond our control we disclaim all liability for the use or handling of this product. This information is offered solely for your consideration, investigation, and verification.