

MATERIAL SAFETY DATA SHEET
830-2506 CAL-TINT®II INTERIOR YELLOW



Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	1 / 12

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Information

Trade name : 830-2506 CAL-TINT®II INTERIOR YELLOW
Use of the Substance / Preparation : Aqueous colorant
Company : Chromaflo Technologies Corporation
2600 Michigan Avenue
Ashtabula, OH 44005-0816
USA

Telephone : 973-929-8000
Telefax : 973-929-8040

US: CHEMTREC EMERGENCY NUMBER : 800-424-9300

CANADA: CANUTEC EMERGENCY NUMBER : 613-996-6666

Product Regulatory Services : 973-929-8060

2. HAZARDS IDENTIFICATION

***** EMERGENCY OVERVIEW *****

Form-paste Color-yellow Odor-Glycol odor.

CAL-TINT colorants may cause eye, skin and respiratory tract irritation.
May be harmful if swallowed.

POTENTIAL HEALTH EFFECTS

Eye contact

According to test results on similar colorant base mixtures, this CAL-TINT colorant is classified as a moderate eye irritant. May cause tearing, reddening and/or swelling.

Skin Contact

CAL-TINT colorants may cause irritation.

Inhalation

CAL-TINT colorants may cause irritation.
Overexposure to aerosols or mists containing ethylene glycol may cause lung irritation. See exposure limit (section 8).

Ingestion

May be harmful if swallowed.

MATERIAL SAFETY DATA SHEET
830-2506 CAL-TINT® II INTERIOR YELLOW



Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	2 / 12

Ingestion of ethylene glycol may cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, irritability and central nervous system effects. Swallowing large volumes of ethylene glycol causes severe kidney damage and cardiopulmonary effects (metabolic acidosis) which may be fatal. The human oral lethal dose is approximately 1.6 g/kg.

Ingestion of ethylene glycol can cause neurological impairment.

Repeated ingestion of ethylene glycol can cause bone marrow, liver, and sperm effects.

Ingestion of excessive amounts of diethylene glycol causes abdominal discomfort or pain, nausea, vomiting, dizziness, central nervous system effects, kidney damage and cardiopulmonary effects (metabolic acidosis) which may be fatal (estimated human oral lethal dose, 1.0 to 1.2 g/kg) and may cause liver effects.

Chronic Health Hazard

Ethylene glycol may aggravate an existing kidney disease. Repeated skin contact with ethylene glycol may, in a very small proportion of cases, cause sensitization with the development of allergic contact dermatitis. The incidence is significantly less than 1% with the undiluted material. Repeated inhalation of ethylene glycol mist may produce signs of central nervous system involvement, particularly dizziness and drowsiness.

Short term exposures to talc may cause lung irritation. Long term excessive exposure to talc dust may cause talcosis, a pulmonary fibrosis which in turn may lead to severe and permanent damage to the lungs. NTP Toxicology and Carcinogenesis Studies of Talc revealed that there is some evidence of carcinogenic activity in male rats and clear evidence of carcinogenic activity in female rats. There was no evidence of carcinogenic activity in male or female mice.

In long term dietary studies of tributyl phosphate in rats, urinary bladder tumors, urinary bladder hyperplasia and increased liver weight were noted. Benign liver tumors, liver enlargement and urinary bladder hyperplasia were observed in long term studies in mice.

Because this product is a free-flowing liquid or paste, dust inhalation is not an expected route of exposure.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Information on ingredients / Hazardous components

Talc, Magnesium silicate hydrate			
CAS-No.	14807-96-6	Percent (Wt./ Wt.)	30 - 60 %
ethanediol; ethylene glycol			
CAS-No.	107-21-1	Percent (Wt./ Wt.)	10 - 30 %
Diethylene glycol			
CAS-No.	111-46-6	Percent (Wt./ Wt.)	5 - 10 %
tributyl phosphate			
CAS-No.	126-73-8	Percent (Wt./ Wt.)	1 - 5 %
NJT SR No.56705700001-5704P			
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	0.1 - 1 %

Other information

This material is classified as hazardous under OSHA regulations.

MATERIAL SAFETY DATA SHEET
830-2506 CAL-TINT® II INTERIOR YELLOW



Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	3 / 12

4. FIRST AID MEASURES

Inhalation

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If unconscious, evaluate the need for artificial respiration. Get immediate medical attention.

Skin contact

Flush skin with plenty of water. Remove contaminated clothing. Obtain medical attention if irritation develops or persists.

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes or until all material has been removed. Obtain medical attention.

Ingestion

If swallowed, get medical attention immediately. Only induce vomiting if directed by a physician. Never give anything by mouth to an unconscious person.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

In case of fire, use water (flood with water), dry chemical, CO2 or "alcohol" foam.

Specific hazards during fire fighting

Contains material that can burn in fire if contained water is evaporated by heat or fire.

Further information

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear. Containers can build up pressure if exposed to heat (fire). Cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear personal protective equipment; see section 8.

Environmental precautions

Obey relevant local, state, provincial and federal laws and regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.

Methods for cleaning up

Ventilate area. Absorb spill with inert material and place in a chemical waste container.

7. HANDLING AND STORAGE

Handling

Safe handling advice

Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid breathing vapor or mist. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Wash thoroughly after handling.

MATERIAL SAFETY DATA SHEET
830-2506 CAL-TINT® II INTERIOR YELLOW



Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	4 / 12

Storage

Requirements for storage areas and containers

Keep in a dry, cool place.
Keep container closed when not in use.
Residual vapors might explode on ignition; do not apply heat, cut, drill, grind or weld on or near this container.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component occupational exposure guidelines

• **tributyl phosphate**

CAS-No.	126-73-8	
Control parameters	0.2 ppm	Time Weighted Average (TWA):(ACGIH)
	5 mg/m ³	PEL:(OSHA Z1)
	0.2 ppm	Time Weighted Average (TWA)
	2.5 mg/m ³	Permissible Exposure Limit (PEL):(US CA OEL)

• **ethanedio; ethylene glycol**

CAS-No.	107-21-1	
	100 mg/m ³	Ceiling Limit Value:(ACGIH)
	Aerosol.	
	40 ppm	Ceiling Limit Value:(US CA OEL)
	100 mg/m ³	
	Vapor.	

• **Talc, Magnesium silicate hydrate**

CAS-No.	14807-96-6	
	2 mg/m ³	Time Weighted Average (TWA):(ACGIH)
	Respirable fraction.	
	The value is for particulate matter containing no asbestos and <1% crystalline silica.	
	2 mg/m ³	Time Weighted Average (TWA)
		Permissible Exposure Limit (PEL):(US CA OEL)
	Respirable dust.	
	20millions of particles per cubic foot of air	Time Weighted Average (TWA):(Z3)
	2.4millions of particles per cubic foot of air	Time Weighted Average (TWA):(Z3)
	Respirable.	
	The exposure limit is calculated from the equation, 250/(%SiO ₂ +5), using a value of 100% SiO ₂ . Lower percentages of SiO ₂ will yield higher exposure limits.	
	0.1 mg/m ³	Time Weighted Average (TWA):(Z3)
	Respirable.	
	The exposure limit is calculated from the equation, 10/(%SiO ₂ +2), using a value of 100% SiO ₂ . Lower percentages of SiO ₂ will yield higher exposure limits.	

MATERIAL SAFETY DATA SHEET**830-2506 CAL-TINT® II INTERIOR YELLOW**

Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	5 / 12

0.3 mg/m³

Time Weighted Average (TWA):(Z3)

Total dust.

The exposure limit is calculated from the equation, 30/(%SiO₂+2), using a value of 100% SiO₂. Lower values of % SiO₂ will give higher exposure limits.

Other Information

The exposure value for ethylene glycol is given as an aerosol.

The AIHA WEEL for diethylene glycol is 50 PPM for total vapor and aerosol and 10 mg/m³ for aerosol alone (eight hour time-weighted averages).

Engineering measures

Use only in well-ventilated areas.

Personal protective equipment**Respiratory protection**

A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.

Hand protection

Use impermeable gloves.

Eye protection

Chemical resistant goggles must be worn.

Skin and body protection

A safety shower and eye wash fountain should be readily available.

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES**Appearance**

Form	paste
Color	yellow
Odor	Glycol odor.

Safety data

pH	8.0 - 9.3
Boiling point/range	> 100 °C
Relative density	1.4
Solubility/qualitative	Solubility in water: Dispersible.
Viscosity, dynamic	70 - 85 KU (25 °C)

Solvents and Volatiles Data

% VOC (gm/l)

590

MATERIAL SAFETY DATA SHEET
830-2506 CAL-TINT® II INTERIOR YELLOW



Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	6 / 12

Evaporation rate Slower than butyl acetate

10. STABILITY AND REACTIVITY

Conditions to avoid Not applicable.

Materials to avoid strong acids, oxidizing substances

 sodium hypochlorite

11. TOXICOLOGICAL INFORMATION

Component Acute oral toxicity ethanediol; ethylene glycol
 107-21-1
 LD50 Rat(female): 4000 mg/kg

 Diethylene glycol
 111-46-6
 LD50 Rat: 20760 mg/kg

 tributyl phosphate
 126-73-8
 LD50 Rat: 1390 mg/kg
 (literature value)

 NJTSR No.56705700001-5704P
 Trade Secret
 LD50 Rat: 5700 mg/kg

Component Acute inhalation tributyl phosphate
toxicity 126-73-8
 LC50 Rat: 28.0 mg/l / 1 h
 (literature value)

Component Acute dermal toxicity ethanediol; ethylene glycol
 107-21-1
 LD50 Rabbit: 10500 mg/kg

 Diethylene glycol
 111-46-6
 LD50 Rabbit: 13300 mg/kg

 tributyl phosphate
 126-73-8
 LD50 Rabbit: > 10000 mg/kg

Component Skin irritation tributyl phosphate
 126-73-8
 Rabbit / 4 h
 slightly irritating

MATERIAL SAFETY DATA SHEET
830-2506 CAL-TINT® II INTERIOR YELLOW



Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	7 / 12

Component Eye irritation
tributyl phosphate
126-73-8
Rabbit
slightly irritating

Component Repeated dose toxicity
Talc, Magnesium silicate hydrate
14807-96-6
Inhalation Rat(male)
Testing period: 791 d
LOAEL: 0.006 mg/l
target organ/effect: Lungs

ethanediol; ethylene glycol
107-21-1

Chronic ingestion of an ingredient in this product has been shown to cause adverse effects on the peripheral nervous system of laboratory animals.

Component Gentoxicity in vitro
tributyl phosphate
126-73-8
In vitro tests have shown mutagenic effects.

Component carcinogenicity assessment
Talc, Magnesium silicate hydrate
14807-96-6
Short term exposures to talc may cause lung irritation. Long term excessive exposure to talc dust may cause talcosis, a pulmonary fibrosis which in turn may lead to severe and permanent damage to the lungs. NTP Toxicology and Carcinogenesis Studies of Talc revealed that there is some evidence of carcinogenic activity in male rats and clear evidence of carcinogenic activity in female rats. There was no evidence of carcinogenic activity in male or female mice.

Component teratogenicity assessment
ethanediol; ethylene glycol
107-21-1
Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. However, there is currently no available information to suggest that ethylene glycol has caused birth defects in humans.

tributyl phosphate
126-73-8
Postnatal and fetotoxic effects have been observed in the presence of maternal toxicity with oral administration in rats.

Component General Toxicity Information
ethanediol; ethylene glycol
107-21-1
Ethylene glycol may aggravate an existing kidney disease. Repeated skin contact with ethylene glycol may, in a very small proportion of cases, cause sensitization with the development of allergic contact dermatitis. The incidence is significantly less than 1% with the undiluted material. Repeated inhalation of ethylene glycol mist may produce signs of central nervous system involvement, particularly dizziness and drowsiness.

MATERIAL SAFETY DATA SHEET
830-2506 CAL-TINT® II INTERIOR YELLOW



Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	8 / 12

Diethylene glycol
111-46-6

According to long-term animal inhalation studies, very high concentrations of diethylene glycol vapors caused central nervous system effects in mice and rats. However, an extensive review of the literature shows that no such effects have been documented in humans (Patty's Industrial Hygiene and Toxicology, 1982, Third Revised Ed., Vol 2c, p 3838).

In a continuous breeding study of mice, continued ingestion of large amounts of diethylene glycol (6 g/kg/day) caused an adverse effect on fertility and some embryotoxic and fetotoxic effects concurrent with some maternal toxicity. The relevance of these very high doses to humans is uncertain.

tributyl phosphate
126-73-8

In long term dietary studies of the alkyl phosphate in rats, urinary bladder tumors, urinary bladder hyperplasia and increased liver weight were noted. Benign liver tumors, liver enlargement and urinary bladder hyperplasia were observed in long term studies in mice.

12. ECOLOGICAL INFORMATION

General Ecological Information No ecotoxicological studies are available.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Advice on disposal

Waste must be disposed of in accordance with federal, state, provincial and local regulations. **CONTAINER DISPOSAL:** Empty containers by removing the top and inverting to allow all free-flowing product to drain. To meet regulatory criteria, the container is considered empty when less than 3% remains in the container. Additional special handling is not typically required and the empty container can be discarded with other non-hazardous trash. Note: Local disposal regulations may be more stringent and require additional restrictions or precautions. Customers should check with their local disposal company, municipal or state authority. Recycle of plastic or metal containers may require clean rather than empty containers. In this case the containers can be rinsed with water until the containers are considered generally product free.

14. TRANSPORT INFORMATION

D.O.T. Road/Rail

Class	9
UN-No	3082
Packing group	III
Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.

MATERIAL SAFETY DATA SHEET
830-2506 CAL-TINT® II INTERIOR YELLOW



Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	9 / 12

Loading Instructions/Remarks

IATA_C	Not dangerous according to transport regulations.
IATA_P	Not dangerous according to transport regulations.
IMDG	Not dangerous according to transport regulations.
CFR_INWTR	USA: Not regulated for transport when package contains less than the reportable quantity listed in section 15 of the msds.
CFR_RAIL	USA: Not regulated for transport when package contains less than the reportable quantity listed in section 15 of the msds.
CFR_ROAD	USA: Not regulated for transport when package contains less than the reportable quantity listed in section 15 of the msds.

15. REGULATORY INFORMATION

Information on ingredients / Non-hazardous components

This product contains the following non-hazardous components

Water			
CAS-No.	7732-18-5	Percent (Wt./ Wt.)	10 - 30 %
NJTSR No.56705700001-5578P			
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	5 - 10 %
ARYL POLYGLYCOL ETHER			
CAS-No.		Percent (Wt./ Wt.)	1 - 5 %
Chlorite			
CAS-No.	71949-90-1	Percent (Wt./ Wt.)	1 - 5 %

US Federal Regulations

OSHA

If listed below, chemical specific standards apply to the product or components:

- None listed

Clean Air Act Section (112)

If listed below, components present at or above the de minimus level are hazardous air pollutants:

- ethanediol; ethylene glycol
CAS-No. 107-21-1

CERCLA Reportable Quantities

If listed below, a reportable quantity (RQ) applies to the product based on the percent of the named component:

- ethanediol; ethylene glycol
CAS-No. 107-21-1
Reportable Quantity 20833 lbs

MATERIAL SAFETY DATA SHEET**830-2506 CAL-TINT® II INTERIOR YELLOW**

Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	10 / 12

SARA Title III Section 311/312 Hazard Categories

The product meets the criteria only for the listed hazard classes:

- Acute Health Hazard
- Chronic Health Hazard

SARA Title III Section 313 Reportable Substances

If listed below, components are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

- ethanediol; ethylene glycol
CAS-No. 107-21-1

Toxic Substances Control Act (TSCA)

If listed below, non-proprietary substances are subject to export notification under Section 12 (b) of TSCA:

- None listed

State Regulations**California Proposition 65**

A warning under the California Drinking Water Act is required only if listed below:

- None listed

MATERIAL SAFETY DATA SHEET
830-2506 CAL-TINT® II INTERIOR YELLOW



Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	11 / 12

International Chemical Inventory Status

Unless otherwise noted, this product is in compliance with the inventory listing of the countries shown below. For information on listing for countries not shown, contact the Product Regulatory Services Department.

- | | |
|--------------------------|---------------------------|
| • Europe (EINECS/ELINCS) | Listed/registered |
| • USA (TSCA) | Listed/registered |
| • Canada (DSL) | Listed/registered |
| • Australia (AICS) | Listed/registered |
| • Japan (MITI) | Not listed/Not registered |
| • Korea (TCCL) | Not listed/Not registered |
| • Philippines (PICCS) | Listed/registered |
| • China | Listed/registered |
| • New Zealand | Listed/registered |

16. OTHER INFORMATION

HMIS Ratings

Health :	2*
Flammability :	1
Physical Hazard :	0

Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

MATERIAL SAFETY DATA SHEET

830-2506 CAL-TINT® II INTERIOR YELLOW



Material no.	99003375	Version	1.33 / US
Specification	139801	Revision date	01/19/2012
Order Number	01969180	Print Date	01/31/2013
		Page	12 / 12

==