

# MATERIAL SAFETY DATA SHEET

## 830-9907 CAL-TINT®II LAMP BLACK



Material no.		Version	2.2 / US
Specification	139644	Revision date	08/31/2011
Order Number		Print Date	04/06/2013
		Page	1 / 11

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### Product information

Trade name : 830-9907 CAL-TINT®II LAMP BLACK  
Use of the Substance / : Aqueous colorant  
Preparation  
Company : Chromaflo Technologies Corporation  
2600 Michigan Avenue  
Ashtabula, OH 44005-0816  
USA

Telephone : 440-997-5137

Telefax : 440-992-3613

US: CHEMTREC EMERGENCY : 800-424-9300  
NUMBER

CANADA: CANUTEC : 613-996-6666  
EMERGENCY NUMBER

Product Regulatory Services : 440-536-9691

### 2. HAZARDS IDENTIFICATION

#### \*\*\* EMERGENCY OVERVIEW \*\*\*

*Form-paste Color-black Odor-Glycol odor.*

CAL-TINT colorants may cause eye, skin and respiratory tract irritation.  
May be harmful if swallowed.

#### POTENTIAL HEALTH EFFECTS

##### Eye contact

Severely irritating.  
May injure eye tissue if not removed promptly.

##### Skin Contact

Moderately irritating.

##### Inhalation

May cause respiratory tract irritation.  
Overexposure to aerosols or mists containing ethylene glycol may cause lung irritation. See exposure limit (section 8).

##### Ingestion

May be harmful if swallowed.

**MATERIAL SAFETY DATA SHEET****830-9907 CAL-TINT®II LAMP BLACK**

Material no.		Version	2.2 / US
Specification	139644	Revision date	08/31/2011
Order Number		Print Date	04/06/2013
		Page	2 / 11

Ingestion of ethylene glycol may cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, irritability and central nervous system effects. Swallowing large volumes of ethylene glycol causes severe kidney damage and cardiopulmonary effects (metabolic acidosis) which may be fatal. The human oral lethal dose is approximately 1.6 g/kg.

Ingestion of ethylene glycol can cause neurological impairment.

Repeated ingestion of ethylene glycol can cause bone marrow, liver, and sperm effects.

Ingestion of excessive amounts of diethylene glycol causes abdominal discomfort or pain, nausea, vomiting, dizziness, central nervous system effects, kidney damage and cardiopulmonary effects (metabolic acidosis) which may be fatal (estimated human oral lethal dose, 1.0 to 1.2 g/kg) and may cause liver effects.

**Chronic Health Hazard**

Ethylene glycol may aggravate an existing kidney disease. Repeated skin contact with ethylene glycol may, in a very small proportion of cases, cause sensitization with the development of allergic contact dermatitis. The incidence is significantly less than 1% with the undiluted material. Repeated inhalation of ethylene glycol mist may produce signs of central nervous system involvement, particularly dizziness and drowsiness.

Short term exposures to talc may cause lung irritation. Long term excessive exposure to talc dust may cause talcosis, a pulmonary fibrosis which in turn may lead to severe and permanent damage to the lungs. NTP Toxicology and Carcinogenesis Studies of Talc revealed that there is some evidence of carcinogenic activity in male rats and clear evidence of carcinogenic activity in female rats. There was no evidence of carcinogenic activity in male or female mice.

Some studies have linked exposure of carbon black dust to lung effects. IARC classifies carbon black as a Category 2B Carcinogen (known animal carcinogen, possible human carcinogen) based on inhalation studies. However, the manufacturers of carbon black state that epidemiologic studies of workers in the carbon black industry in the U.S. and W. Europe show no significant adverse health effects due to occupational exposure.

Because this product is a free-flowing liquid or paste, dust inhalation is not an expected route of exposure.

**3. COMPOSITION/INFORMATION ON INGREDIENTS****Information on ingredients / Hazardous components**

Carbon black, amorphous			
CAS-No.	1333-86-4	Percent (Wt./ Wt.)	10 - 30 %
NJTSR No.	56705700001-5043P		
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	5 - 10 %
ethanediol; ethylene glycol			
CAS-No.	107-21-1	Percent (Wt./ Wt.)	10 - 30 %
Diethylene glycol			
CAS-No.	111-46-6	Percent (Wt./ Wt.)	1 - 5 %
Talc, Magnesium silicate hydrate			
CAS-No.	14807-96-6	Percent (Wt./ Wt.)	10 - 30 %
Distillates (petroleum), hydrotreated light; Kerosine - unspecified			
CAS-No.	64742-47-8	Percent (Wt./ Wt.)	0.01 - 1 %
NJTSR No.	56705700001-5704P		
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	1 - 5 %

**MATERIAL SAFETY DATA SHEET****830-9907 CAL-TINT®II LAMP BLACK**

Material no.		Version	2.2 / US
Specification	139644	Revision date	08/31/2011
Order Number		Print Date	04/06/2013
		Page	3 / 11

**Other information**

This material is classified as hazardous under OSHA regulations.

**4. FIRST AID MEASURES****Inhalation**

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If unconscious, evaluate the need for artificial respiration. Get immediate medical attention.

**Skin contact**

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Obtain medical attention. Wash clothing before reuse. Destroy or thoroughly clean contaminated shoes before reuse.

**Eye contact**

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.

**Ingestion**

If swallowed, get medical attention immediately. Only induce vomiting if directed by a physician. Never give anything by mouth to an unconscious person.

**5. FIRE-FIGHTING MEASURES**

Flash point not determined

**Suitable extinguishing media**

In case of fire, use water (flood with water), dry chemical, CO2 or "alcohol" foam.

**Specific hazards during fire fighting**

Contains material that can burn in fire if contained water is evaporated by heat or fire.

**Further information**

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear. Containers can build up pressure if exposed to heat (fire). Cool with water spray.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions**

Wear personal protective equipment; see section 8.

**Environmental precautions**

Obey relevant local, state, provincial and federal laws and regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.

**Methods for cleaning up**

Ventilate area. Absorb spill with inert material and place in a chemical waste container.

**MATERIAL SAFETY DATA SHEET****830-9907 CAL-TINT®II LAMP BLACK**

Material no.		Version	2.2 / US
Specification	139644	Revision date	08/31/2011
Order Number		Print Date	04/06/2013
		Page	4 / 11

**7. HANDLING AND STORAGE****Handling****Safe handling advice**

Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid breathing vapor or mist. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Wash thoroughly after handling.

**Storage****Requirements for storage areas and containers**

Keep in a dry, cool place.  
Keep container closed when not in use.  
Residual vapors might explode on ignition; do not apply heat, cut, drill, grind or weld on or near this container.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Component occupational exposure guidelines****• Carbon black, amorphous**

CAS-No.	1333-86-4	PEL:(OSHA Z1)
Control parameters	3.5 mg/m3	Time Weighted Average (TWA)
	3.5 mg/m3	Permissible Exposure Limit (PEL):(US CA OEL)
	3 mg/m3	Time Weighted Average (TWA):(ACGIH)
	Inhalable fraction.	

**• ethanediol; ethylene glycol**

CAS-No.	107-21-1	Ceiling Limit Value:(ACGIH)
	100 mg/m3	
	Aerosol.	
	40 ppm	Ceiling Limit Value:(US CA OEL)
	100 mg/m3	
	Vapor.	

**• Talc, Magnesium silicate hydrate**

CAS-No.	14807-96-6	Time Weighted Average (TWA):(ACGIH)
	2 mg/m3	
	Respirable fraction.	
	The value is for particulate matter containing no asbestos and <1% crystalline silica.	
	2 mg/m3	Time Weighted Average (TWA)
		Permissible Exposure Limit (PEL):(US CA OEL)
	Respirable dust.	
	20millions of particles	Time Weighted Average (TWA):(Z3)

**MATERIAL SAFETY DATA SHEET****830-9907 CAL-TINT®II LAMP BLACK**

Material no.		Version	2.2 / US
Specification	139644	Revision date	08/31/2011
Order Number		Print Date	04/06/2013
		Page	5 / 11

per cubic foot of air  
2.4millions of particles  
per cubic foot of air  
Respirable.

Time Weighted Average (TWA):(Z3)

The exposure limit is calculated from the equation,  $250/(\%SiO_2+5)$ , using a value of 100% SiO<sub>2</sub>. Lower percentages of SiO<sub>2</sub> will yield higher exposure limits.

0.1 mg/m<sup>3</sup>  
Respirable.

Time Weighted Average (TWA):(Z3)

The exposure limit is calculated from the equation,  $10/(\%SiO_2+2)$ , using a value of 100% SiO<sub>2</sub>. Lower percentages of SiO<sub>2</sub> will yield higher exposure limits.

0.3 mg/m<sup>3</sup>  
Total dust.

Time Weighted Average (TWA):(Z3)

The exposure limit is calculated from the equation,  $30/(\%SiO_2+2)$ , using a value of 100% SiO<sub>2</sub>. Lower values of % SiO<sub>2</sub> will give higher exposure limits.

**Other information**

The exposure value for ethylene glycol is given as an aerosol.

The AIHA WEEL for diethylene glycol is 50 PPM for total vapor and aerosol and 10 mg/m<sup>3</sup> for aerosol alone (eight hour time-weighted averages).

The OSHA TWA and ACGIH TWA exposure values for talc are for asbestos free talc expressed as millions of particles per cubic foot (mppcf).

**Engineering measures**

Use only in well-ventilated areas.

**Personal protective equipment****Respiratory protection**

A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.

**Hand protection**

Use impermeable gloves.

**Eye protection**

Chemical resistant goggles must be worn.

**Skin and body protection**

A safety shower and eye wash fountain should be readily available.

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES****Appearance**

Form	paste
Color	black
Odor	Glycol odor.

**MATERIAL SAFETY DATA SHEET****830-9907 CAL-TINT®II LAMP BLACK**

Material no.		Version	2.2 / US
Specification	139644	Revision date	08/31/2011
Order Number		Print Date	04/06/2013
		Page	6 / 11

**Safety data**

pH	8.0 - 9.0
Boiling point/range	> 100 °C
Flash point	not determined
Relative density	1.4
Solubility/qualitative	Solubility in water: Dispersible.
Viscosity, dynamic	75 - 90 KU (25 °C)
Solvents and Volatiles Data	
	% VOC (gm/l) 439
Evaporation rate	Slower than butyl acetate

**10. STABILITY AND REACTIVITY**

Conditions to avoid	Not applicable.
Materials to avoid	strong acids, oxidizing substances sodium hypochlorite
Further information	Stable under normal conditions.

**11. TOXICOLOGICAL INFORMATION**

Component Acute oral toxicity	Carbon black, amorphous 1333-86-4 LD50 Rat: > 10000 mg/kg  NJTSR No.56705700001-5043P Trade Secret LD50 Rat: 3000 mg/kg  ethanediol; ethylene glycol 107-21-1 LD50 Rat(female): 4000 mg/kg  Diethylene glycol 111-46-6 LD50 Rat: 20760 mg/kg  Distillates (petroleum), hydrotreated light; Kerosine - unspecified 64742-47-8 LD50 Rat: > 15000 mg/kg
-------------------------------	--

**MATERIAL SAFETY DATA SHEET****830-9907 CAL-TINT®II LAMP BLACK**

Material no.		Version	2.2 / US
Specification	139644	Revision date	08/31/2011
Order Number		Print Date	04/06/2013
		Page	7 / 11

NJTSR No.56705700001-5704P

Trade Secret

LD50 Rat: 5700 mg/kg

Component Acute inhalation toxicity

Carbon black, amorphous

1333-86-4

LC50 Rat: 6750 mg/m3 / 4 h

Distillates (petroleum), hydrotreated light; Kerosine - unspecified

64742-47-8

LC50 Rat: &gt; 14100 mg/m3 / 4 h

Component Acute dermal toxicity

NJTSR No.56705700001-5043P

Trade Secret

LD50 Rabbit: 4400 mg/kg

ethanediol; ethylene glycol

107-21-1

LD50 Rabbit: 10500 mg/kg

Diethylene glycol

111-46-6

LD50 Rabbit: 13300 mg/kg

Distillates (petroleum), hydrotreated light; Kerosine - unspecified

64742-47-8

LD50 Rabbit: &gt; 2000 mg/kg

Component Repeated dose toxicity

ethanediol; ethylene glycol

107-21-1

Chronic ingestion of an ingredient in this product has been shown to cause adverse effects on the peripheral nervous system of laboratory animals.

Talc, Magnesium silicate hydrate

14807-96-6

Inhalation Rat(male)

Testing period: 791 d

LOAEL: 0.006 mg/l

target organ/effect: Lungs

Component Mutagenicity assessment

Carbon black, amorphous

1333-86-4

This product contains one or more ingredients that have been shown to produce mutagenic effects in in vitro testing.

Component carcinogenicity assessment

Carbon black, amorphous

1333-86-4

Some studies have linked exposure of carbon black dust to lung effects. IARC classifies carbon black as a Category 2B Carcinogen (known animal carcinogen, possible human carcinogen) based on inhalation studies. However, the manufacturers of carbon black state that epidemiologic studies of workers in the carbon black industry in the U.S. and W. Europe show no significant adverse health effects due to occupational exposure.

**MATERIAL SAFETY DATA SHEET****830-9907 CAL-TINT®II LAMP BLACK**

Material no.		Version	2.2 / US
Specification	139644	Revision date	08/31/2011
Order Number		Print Date	04/06/2013
		Page	8 / 11

Talc, Magnesium silicate hydrate  
14807-96-6

Short term exposures to talc may cause lung irritation. Long term excessive exposure to talc dust may cause talcosis, a pulmonary fibrosis which in turn may lead to severe and permanent damage to the lungs. NTP Toxicology and Carcinogenesis Studies of Talc revealed that there is some evidence of carcinogenic activity in male rats and clear evidence of carcinogenic activity in female rats. There was no evidence of carcinogenic activity in male or female mice.

Component teratogenicity  
assessment

ethanediol; ethylene glycol  
107-21-1

Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. However, there is currently no available information to suggest that ethylene glycol has caused birth defects in humans.

Component General Toxicity  
Information

ethanediol; ethylene glycol  
107-21-1

Ethylene glycol may aggravate an existing kidney disease. Repeated skin contact with ethylene glycol may, in a very small proportion of cases, cause sensitization with the development of allergic contact dermatitis. The incidence is significantly less than 1% with the undiluted material. Repeated inhalation of ethylene glycol mist may produce signs of central nervous system involvement, particularly dizziness and drowsiness.

Diethylene glycol  
111-46-6

According to long-term animal inhalation studies, very high concentrations of diethylene glycol vapors caused central nervous system effects in mice and rats. However, an extensive review of the literature shows that no such effects have been documented in humans (Patty's Industrial Hygiene and Toxicology, 1982, Third Revised Ed., Vol 2c, p 3838). In a continuous breeding study of mice, continued ingestion of large amounts of diethylene glycol (6 g/kg/day) caused an adverse effect on fertility and some embryotoxic and fetotoxic effects concurrent with some maternal toxicity. The relevance of these very high doses to humans is uncertain.

---

**12. ECOLOGICAL INFORMATION**

General Ecological Information      No ecotoxicological studies are available.

---

**13. DISPOSAL CONSIDERATIONS****WASTE DISPOSAL**

Advice on disposal

Waste must be disposed of in accordance with federal, state, provincial and local regulations. CONTAINER DISPOSAL: Empty containers by



**MATERIAL SAFETY DATA SHEET****830-9907 CAL-TINT®II LAMP BLACK**

Material no.		Version	2.2 / US
Specification	139644	Revision date	08/31/2011
Order Number		Print Date	04/06/2013
		Page	9 / 11

removing the top and inverting to allow all free-flowing product to drain. To meet regulatory criteria, the container is considered empty when less than 3% remains in the container. Additional special handling is not typically required and the empty container can be discarded with other non-hazardous trash. Note: Local disposal regulations may be more stringent and require additional restrictions or precautions. Customers should check with their local disposal company, municipal or state authority. Recycle of plastic or metal containers may require clean rather than empty containers. In this case the containers can be rinsed with water until the containers are considered generally product free.

**14. TRANSPORT INFORMATION****D.O.T. Road/Rail**

Class	9
UN-No	3082
Packing group	III
Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.

**Loading instructions/Remarks**

IATA_C	Not dangerous according to transport regulations.
IATA_P	Not dangerous according to transport regulations.
IMDG	Not dangerous according to transport regulations.
CFR_INWTR	USA: Not regulated for transport when package contains less than the reportable quantity listed in section 15 of the msds.
CFR_RAIL	USA: Not regulated for transport when package contains less than the reportable quantity listed in section 15 of the msds.
CFR_ROAD	USA: Not regulated for transport when package contains less than the reportable quantity listed in section 15 of the msds.

**15. REGULATORY INFORMATION****Information on ingredients / Non-hazardous components**

This product contains the following non-hazardous components

Water			
CAS-No.	7732-18-5	Percent (Wt./ Wt.)	10 - 30 %
NJTSR No.	56705700001-5032P		
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	1 - 5 %

**US Federal Regulations****OSHA**

If listed below, chemical specific standards apply to the product or components:

- None listed

**MATERIAL SAFETY DATA SHEET****830-9907 CAL-TINT®II LAMP BLACK**

Material no.		Version	2.2 / US
Specification	139644	Revision date	08/31/2011
Order Number		Print Date	04/06/2013
		Page	10 / 11

**Clean Air Act Section (112)**

If listed below, components present at or above the de minimus level are hazardous air pollutants:

- ethanediol; ethylene glycol  
CAS-No. 107-21-1

**CERCLA Reportable Quantities**

If listed below, a reportable quantity (RQ) applies to the product based on the percent of the named component:

- ethanediol; ethylene glycol  
CAS-No. 107-21-1  
Reportable Quantity 27174 lbs

**SARA Title III Section 311/312 Hazard Categories**

The product meets the criteria only for the listed hazard classes:

- Acute Health Hazard
- Chronic Health Hazard

**SARA Title III Section 313 Reportable Substances**

If listed below, components are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

- ethanediol; ethylene glycol  
CAS-No. 107-21-1

**Toxic Substances Control Act (TSCA)**

If listed below, non-proprietary substances are subject to export notification under Section 12 (b) of TSCA:

- None listed

**State Regulations****California Proposition 65**

A warning under the California Drinking Water Act is required only if listed below:

WARNING! This product contains a chemical known in the State of California to cause cancer.

- Carbon black, amorphous  
CAS-No. 1333-86-4

**MATERIAL SAFETY DATA SHEET****830-9907 CAL-TINT®II LAMP BLACK**

Material no.		Version	2.2 / US
Specification	139644	Revision date	08/31/2011
Order Number		Print Date	04/06/2013
		Page	11 / 11

**International Chemical Inventory Status**

Unless otherwise noted, this product is in compliance with the inventory listing of the countries shown below. For information on listing for countries not shown, contact the Product Regulatory Services Department.

- |                          |                           |
|--------------------------|---------------------------|
| • Europe (EINECS/ELINCS) | Listed/registered         |
| • USA (TSCA)             | Listed/registered         |
| • Canada (DSL)           | Listed/registered         |
| • Australia (AICS)       | Listed/registered         |
| • Japan (MITI)           | Not listed/Not registered |
| • Korea (TCCL)           | Not listed/Not registered |
| • Philippines (PICCS)    | Listed/registered         |
| • China                  | Listed/registered         |
| • New Zealand            | Listed/registered         |

**16. OTHER INFORMATION****HMIS Ratings**

Health :	2*
Flammability :	1
Physical Hazard :	0

**Further information**

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.