

# SAFETY DATA SHEET

## TransTint Brown Mahogany #6008

### Section 1. Identification

**GHS product identifier** : TransTint Brown Mahogany #6008  
**Product code** : Not available.  
**Other means of identification** : Not available.  
**Product type** : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Surface Decoration and Colorant

**Supplier's details** : J.B. Jewitt Co., Inc  
 1935 W 96th St., Unit Q  
 Cleveland, OH 44102  
 Tel: 216-631-5309  
 Toll free: 866-631-5429  
 Fax: 216-631-5429  
 Email: jbjewitt@gmail.com  
 Website: www.homesteadfinishingproducts.com

**Emergency telephone number (with hours of operation)** : 216-631-5309  
 9 AM EST to 4 PM EST

### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 4  
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
 SKIN SENSITIZATION - Category 1  
 CARCINOGENICITY - Category 2  
 AQUATIC HAZARD (ACUTE) - Category 2  
 AQUATIC HAZARD (LONG-TERM) - Category 2

#### GHS label elements

##### Hazard pictograms



**Signal word** : Warning

**Hazard statements** : H227 - Combustible liquid.  
 H317 - May cause an allergic skin reaction.  
 H319 - Causes serious eye irritation.  
 H351 - Suspected of causing cancer.  
 H411 - Toxic to aquatic life with long lasting effects.



## Section 2. Hazards identification

### Precautionary statements

#### Prevention

- : P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P280 - Wear protective gloves, protective clothing and eye or face protection.
- P210 - Keep away from flames and hot surfaces. No smoking.
- P273 - Avoid release to the environment.
- P261 - Avoid breathing vapor.
- P264 - Wash thoroughly after handling.
- P272 - Contaminated work clothing must not be allowed out of the workplace.

#### Response

- : P391 - Collect spillage.
- P308 + P313 - IF exposed or concerned: Get medical advice or attention.
- P363 - Wash contaminated clothing before reuse.
- P302 + P352 - IF ON SKIN: Wash with plenty of water.
- P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 - If eye irritation persists: Get medical advice or attention.

#### Storage

- : P405 - Store locked up.
- P403 + P235 - Store in a well-ventilated place. Keep cool.

#### Disposal

- : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### Hazards not otherwise classified

- : None known.

## Section 3. Composition/information on ingredients

#### Substance/mixture

- : Mixture

#### Other means of identification

- : Not available.

Ingredient name	%	CAS number
2-(Propyloxy)ethanol	≥25 - ≤50	2807-30-9
2-(2-Butoxyethoxy)ethanol	≥10 - ≤25	112-34-5
Tetrasodium bis[2-[[[3-[[1-[(2-chloroanilino)carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulphonyl]amino]benzoato(3-)]cobaltate(4-)	≥5 - ≤10	70851-34-2
Propane-1,2-diol	≥3 - ≤5	57-55-6
1-Methoxy-2-propanol	≥3 - ≤5	107-98-2
Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)][3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(2-)	≥1 - ≤3	70236-60-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**



## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : This product contains Cr+3 compounds. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No known significant effects or critical hazards.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : This product contains Cr+3 compounds. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.



## Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
sulfur oxides  
halogenated compounds  
metal oxide/oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up



## Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.



## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
2-(Propyloxy)ethanol 2-(2-Butoxyethoxy)ethanol	None. <b>ACGIH TLV (United States, 3/2019).</b> TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor
Tetrasodium bis[2-[[[3-[[1-[(2-chloroanilino)carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulphonyl]amino]benzoato(3-)]cobaltate(4-)	<b>ACGIH TLV (United States, 3/2020). Skin sensitizer. Inhalation sensitizer.</b> TWA: 0.02 mg/m <sup>3</sup> , (as Co) 8 hours.
Propane-1,2-diol	<b>AIHA WEEL (United States, 7/2018).</b> TWA: 10 mg/m <sup>3</sup> 8 hours.
1-Methoxy-2-propanol	<b>ACGIH TLV (United States, 3/2019).</b> TWA: 50 ppm 8 hours. TWA: 184 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 369 mg/m <sup>3</sup> 15 minutes. <b>NIOSH REL (United States, 10/2016).</b> TWA: 100 ppm 10 hours. TWA: 360 mg/m <sup>3</sup> 10 hours. STEL: 150 ppm 15 minutes. STEL: 540 mg/m <sup>3</sup> 15 minutes.
Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)] [3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(2-)	<b>NIOSH REL (United States, 10/2016).</b> TWA: 0.5 mg/m <sup>3</sup> , (as CR) 8 hours. <b>OSHA PEL (United States, 5/2018).</b> TWA: 0.5 mg/m <sup>3</sup> , (as Cr) 8 hours.

### Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

### Individual protection measures

#### Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

#### Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

## Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Color** : Dark Brown.
- Odor** : Ether-like.
- Odor threshold** : Not available.
- pH** : 6 to 10
- Melting/freezing point** : Not available.
- Initial boiling point and boiling range** : <110°C (<230°F)
- Flash point** : Closed cup: 71°C (159.8°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : 1.06
- Solubility** : Not available.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.
- Flow time (ISO 2431)** : Not available.

## Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.



## Section 10. Stability and reactivity

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**Incompatible materials** : None known.

**Hazardous decomposition products** : Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide, nitrogen oxides (NOx), other toxic vapors.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-(Propyloxy)ethanol	LD50 Oral	Rat	3089 mg/kg	-
2-(2-Butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
Propane-1,2-diol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
1-Methoxy-2-propanol	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(Propyloxy)ethanol	Eyes - Severe irritant	Rabbit	-	24 hours 750 µg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Guinea pig	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
2-(2-Butoxyethoxy)ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
1-Methoxy-2-propanol	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

#### Sensitization

There is no data available.

#### Mutagenicity

There is no data available.

#### Carcinogenicity

##### Classification

Product/ingredient name	OSHA	IARC	NTP
Tetrasodium bis[2-[[[3-[[1-(2-chloroanilino)carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulphonyl]amino]benzoato(3-)]cobaltate (4-)	-	2B	Reasonably anticipated to be a human carcinogen.
Disodium [2,4-dihydro-4-(2-hydroxy-5-nitrophenyl)azo]	-	3	-



## Section 11. Toxicological information

-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)]  
[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]  
-7-nitronaphthalene-1-sulphonato(3-)]chromate (2-)

### Reproductive toxicity

There is no data available.

### Teratogenicity

There is no data available.

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
1-Methoxy-2-propanol	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

There is no data available.

### Aspiration hazard

There is no data available.

**Information on the likely routes of exposure** : Routes of entry anticipated: Oral, Dermal, Inhalation.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : May cause an allergic skin reaction.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness  
**Ingestion** : No known significant effects or critical hazards.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : No known significant effects or critical hazards.  
**Potential delayed effects** : No known significant effects or critical hazards.

#### Long term exposure



## Section 11. Toxicological information

**Potential immediate effects** : No known significant effects or critical hazards.

**Potential delayed effects** : No known significant effects or critical hazards.

### Potential chronic health effects

**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
TransTint Brown Mahogany #6008	N/A	3221.6	N/A	N/A	N/A
2-(Propyloxy)ethanol	3089	1100	N/A	N/A	N/A
2-(2-Butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A
Propane-1,2-diol	20000	20800	N/A	N/A	N/A
1-Methoxy-2-propanol	6600	13000	N/A	N/A	N/A

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
2-(2-Butoxyethoxy)ethanol	Acute LC50 1300000 µg/L Fresh water	Fish - Lepomis macrochirus	96 hours
Propane-1,2-diol	Acute EC50 >110 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1020000 µg/L Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 710000 µg/L Fresh water	Fish - Pimephales promelas	96 hours

### Persistence and degradability

There is no data available.

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2-(Propyloxy)ethanol	0.673	-	low
2-(2-Butoxyethoxy)ethanol	1	-	low
Propane-1,2-diol	-1.07	-	low
1-Methoxy-2-propanol	<1	-	low
Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)] [3-hydroxy-4-[(2-hydroxy-	-0.075	-	low



## Section 12. Ecological information

1-naphthyl)azo]  
-7-nitronaphthalene-  
1-sulphonato(3-)]chromate(2-)

### Mobility in soil



**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	DOT Classification	IMDG	IATA
<b>UN number</b>	NA1993	UN3082	UN3082
<b>UN proper shipping name</b>	COMBUSTIBLE LIQUID, N.O.S. (2-(Propyloxy)ethanol, 2-(2-Butoxyethoxy)ethanol)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetrasodium bis[2-[[[3-[[1-[(2-chloroanilino)carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulphonyl]amino]benzoato(3-)]cobaltate (4-), Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)]-[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(2-))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetrasodium bis[2-[[[3-[[1-[(2-chloroanilino)carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulphonyl]amino]benzoato(3-)]cobaltate (4-), Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)]-[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(2-))
<b>Transport hazard class(es)</b>	Combustible liquid.	9 	9 
<b>Packing group</b>	III	III	III



## Section 14. Transport information

Environmental hazards	No.	Yes.	Yes.
-----------------------	-----	------	------

AERG : 128

### Additional information

- DOT Classification** : Non-bulk packages (less than or equal to 119 gal) of combustible liquids are not regulated as hazardous materials.
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations** : **TSCA 8(a) CDR Exempt/Partial exemption:** Not determined  
**Clean Water Act (CWA) 307:** Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)][3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(2-)

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : FLAMMABLE LIQUIDS - Category 4  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 2

#### Composition/information on ingredients



## Section 15. Regulatory information

Name	%	Classification
2-(Propyloxy)ethanol	≥25 - ≤50	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
2-(2-Butoxyethoxy)ethanol	≥10 - ≤25	FLAMMABLE LIQUIDS - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
Tetrasodium bis[2-[[[3-[[1-(2-chloroanilino)carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulphonyl]amino]benzoato(3-)]cobaltate(4-)	≥5 - ≤10	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2
1-Methoxy-2-propanol	≥3 - ≤5	FLAMMABLE LIQUIDS - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)][3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(2-)	≥1 - ≤3	SKIN SENSITIZATION - Category 1B

### SARA 313

	Product name	CAS number	%
<b>Form R - Reporting requirements</b>	2-(Propyloxy)ethanol	2807-30-9	≥25 - ≤50
	2-(2-Butoxyethoxy)ethanol	112-34-5	≥10 - ≤25
	Tetrasodium bis[2-[[[3-[[1-(2-chloroanilino)carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulphonyl]amino]benzoato(3-)]cobaltate(4-)	70851-34-2	≥5 - ≤10
	Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)][3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(2-)	70236-60-1	≥1 - ≤3
<b>Supplier notification</b>	2-(Propyloxy)ethanol	2807-30-9	≥25 - ≤50
	2-(2-Butoxyethoxy)ethanol	112-34-5	≥10 - ≤25
	Tetrasodium bis[2-[[[3-[[1-(2-chloroanilino)carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulphonyl]amino]benzoato(3-)]cobaltate(4-)	70851-34-2	≥5 - ≤10
	Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)][3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(2-)	70236-60-1	≥1 - ≤3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

#### Massachusetts

: The following components are listed: 1-Methoxy-2-propanol

#### New York

: None of the components are listed.



## Section 15. Regulatory information

- New Jersey** : The following components are listed: 2-(Propyloxy)ethanol; 2-(2-Butoxyethoxy)ethanol; Propane-1,2-diol; 1-Methoxy-2-propanol; Tetrasodium bis[2-[[[3-[[1-[(2-chloroanilino)carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulphonyl]amino]benzoato(3-)]cobaltate(4-); Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)][3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(2-)
- Pennsylvania** : The following components are listed: Propane-1,2-diol; 1-Methoxy-2-propanol; Tetrasodium bis[2-[[[3-[[1-[(2-chloroanilino)carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulphonyl]amino]benzoato(3-)]cobaltate(4-); Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)][3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(2-)

### California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

**United States (TSCA 8b)** : Not determined.

## Section 16. Other information

### Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 AQUATIC HAZARD (ACUTE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

### History

- Date of issue/Date of revision** : 03/15/2021
- Date of previous issue** : Not applicable
- Version** : 1
- Prepared by** : KMK Regulatory Services Inc.

## Section 16. Other information

### Key to abbreviations

- : ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- N/A = Not available
- SGG = Segregation Group
- UN = United Nations

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

